

Code of practice

Mines survey



Department of
Industry and Resources
Safety and Health Division



Code of practice Mines survey



Department of
Industry and Resources
Safety and Health Division



Reference

The recommended reference for this publication is:
Department of Industry and Resources, 2005, Mines survey — code of practice: Safety and Health Division, Department of Industry and Resources, Western Australia, 20 pp.

ISBN 0 9757415 3 5

© Department of Industry and Resources 2005

Except where the Copyright Act otherwise allows, reproduction in whole or part of this publication will be permitted only with the prior written permission of the Department of Industry and Resources. Applications for permission should be addressed to the General Manager, Communications and Marketing Division.

Surveying photographs on the cover are published with permission from Mining Engineering and Mine Surveying Department, Western Australian School of Mines.

This publication is also available in digital format (PDF) online at www.doir.wa.gov.au/safety-pubs.

Further details of publications produced by the Safety and Health Division can be obtained by contacting:

Safety and Health Division — Publications
Department of Industry and Resources
Mineral House
100 Plain Street
EAST PERTH WA 6004

Telephone: +61 8 9222 3229
Facsimile: +61 8 9325 2280
Email: shed@doir.wa.gov.au

Disclaimer

The information contained in this publication is provided in good faith and believed to be reliable and accurate at the time of publication. However, the information is provided on the basis that the reader will be solely responsible for assessing the information and its veracity and usefulness.

The State shall in no way be liable, in negligence or howsoever, for any loss sustained or incurred by anyone relying on the information, even if such information is or turns out to be wrong, incomplete, out-of-date or misleading.

In this disclaimer:

State means the State of Western Australia and includes every Minister, agent, agency, department, statutory body corporate and instrumentality thereof and each employee or agent of any of them.

Information includes information, data, representations, advice, statements and opinions, expressly or implied set out in this publication.

Loss includes loss, damage, liability, cost, expense, illness and injury (including death).



Contents

Foreword	iv	3 Mine plan	6
1 Introduction	1	3.1 Authorisation of plan.....	6
1.1 Application.....	1	3.2 Preparation of plan.....	6
1.2 Preparation.....	1	3.3 Composition of plan.....	6
1.3 Compilation.....	1	3.4 Preparation by digital methods.....	6
1.4 Conversion to MGA94.....	1	3.5 Manually drafted plans.....	7
1.5 Symbols.....	2	3.6 Additional information.....	7
2 Survey standards and procedures	3	3.7 Endorsement of plan.....	7
2.1 Overview of survey standards and procedures.....	3	3.8 Action upon discontinuance or abandonment.....	7
2.2 Origin of coordinates.....	3	3.9 Cessation of duties of the appointed mines surveyor.....	8
2.3 Surface baseline.....	3	3.10 Other plans required.....	8
2.4 Underground baseline.....	3	3.11 Plan lodgement requirements.....	9
2.5 Traverses.....	3	4 Mine plan format and information	10
2.6 Correlation of surface and underground surveys.....	4	Appendix 1 — Legislative framework	14
2.7 Accuracy of levelling.....	4	Appendix 2 — Glossary	18
2.8 Survey records and supply of survey information.....	4		
2.9 Requirements when workings are to become inaccessible.....	5		
2.10 Maintenance and adjustment of survey equipment.....	5		



Foreword

Codes of practice

A code of practice provides practical guidance on how to comply with a general duty under the *Mines Safety and Inspection Act 1994* or a specific duty under the Mines Safety and Inspection Regulations 1995. It describes, without being prescriptive, safe work practices that can be used to reduce the risk of work-related injury and disease.

Work practices included may not represent the only acceptable means of achieving the standard to which the code refers.

Compliance with codes of practice is not mandatory but they may be used by courts as the standard when assessing other methods or practices used.

The *Mines Safety and Inspection Act 1994* established the Mines Occupational Safety and Health Advisory Board (MOSHAB) comprising representatives of employers, employees, unions and government. MOSHAB has the function of advising and making recommendations to the Minister for State Development on occupational safety and health matters concerning the minerals industry in Western Australia.

MOSHAB is also empowered to prepare or recommend the adoption of codes of practice, guidelines, standards, specifications or other forms of guidance for the purpose of assisting employers, employees or manufacturers to maintain appropriate standards of occupational safety and health in the minerals industry.

This code of practice was developed by the Mines Survey Board and submitted to MOSHAB. It is issued by the Department of Industry and Resources under the *Mines Safety and Inspection Act 1994*, with endorsement by MOSHAB and approval from the Minister.

The Act

The *Mines Safety and Inspection Act 1994* sets objectives to promote and improve occupational safety and health standards within the minerals industry.

The Act sets out broad duties, and is supported by a further tier of statute, commonly referred to as regulations, together with lower tiers of non-statutory codes of practice and guidelines.

Regulations

The Act is supported by regulations, which provide more specific requirements for a range of activities. Like the Act, regulations are enforceable and breaches may result in prosecution, fines or directions to cease operations and undertake remedial action.

Application

The provisions of this code of practice apply to all mines as defined in the Act, s. 4(1).

Who should use this code of practice?

This code of practice should be used by all mine surveyors employed on mine sites in Western Australia and in particular:

- in underground mining operations
- on surface mining operations.



1 Introduction

1.1 Application

This code of practice is to be used in the compilation of a mine plan for each mining operation. The legislative basis for the code is outlined in Appendix 1, and definitions and abbreviations are listed in Appendix 2.

A mine plan consists of any number of sheets showing the entire workings of a mine in plan and section. Each sheet will represent a part or whole of one or more mining horizons or an area of the mining or quarrying operation shown in plan. The mine plan as defined in this code of practice includes any cross section or longitudinal section sheets used.

Other plans may be required as set out in Section 3 of this code of practice.

There is also a need to keep a survey book in the survey office. This book should be in hard copy and should comply with requirements of the Act, s. 89. This does not prevent the same information being stored in electronic form in addition to the hard copy. Results of survey department audits can be noted in this book, as well as records of significant survey information.

1.2 Preparation

This code of practice provides for both the 3D digital and 2D non-digital recording, preparation and storage of a mine plan.

1.3 Compilation

So far as is practicable, and particularly for new mines, the mine plan should be compiled on the Map Grid of Australia 1994 (MGA94) based on the Geocentric Datum of Australia 1994 (GDA94) values. Otherwise the connection between local grid and MGA94 needs to be documented in the survey book, along with local false origin and datum details.

The mine plan should be sectionalised into sheets conforming to a referenced index that is documented in the survey book, while complying with sheet format and maximum scale requirements as recommended.

All plans used in the compilation of the mine plan should be regarded with suspicion until their accuracy has been verified. A documented effort should be made to obtain all existing information about the extents and location of old workings. This documentation should be referenced in the survey book.

Where old workings are known to exist and where they may constitute a danger to proposed or existing development, they should be clearly shown and annotated on the mine plan, stating the workings contain water or fill, until the contrary has been proved.

Workings that have become inaccessible or may constitute a hazard (i.e. bad ground, caving, no road), should be annotated on the mine plan by the authorised mine surveyor. The annotation should correctly describe the condition rendering the ground inaccessible or dangerous.

1.4 Conversion to MGA94

It is recommended that the transformation of the mine plan to the MGA94 should occur. This may not, however, be practicable for mines with extensive workings. It is suggested that new mines begin with MGA94.

If the mine plan is transformed to the MGA94, all information and detail on the existing mine plan must be transferred to the new plan. The date of transformation of the mine plan to MGA94 must be documented in the survey book and precautions taken to ensure that the old plan is archived and no longer updated.

An existing mine operating to a local grid and height datum must show the relationship between the local grid and height datum, and MGA94 and Australian Height Datum 1971 (AHD) as required under the Mines Safety and Inspection Regulations 1995, r. 3.50(2). This relationship should be recorded in the survey book.

A notation should appear on the mine plan as to the location of any additional information relevant to the mine plan, including reference to any datum used. This additional information is to be recorded in the survey book.

Sufficient points of known coordinate value in both the local mine grid and MGA94 must be provided to allow



transformation of the mine plan onto the MGA94 grid. The datum reference points should be chosen to give a broad coverage of the mine lease area. This additional information is to be stored in the survey book.

1.5 Symbols

It is recommended that the technical symbols, sign conventions and definitions for strata to be shown on the mine plan should be detailed in records in the survey book.



2 Survey standards and procedures

2.1 Overview of survey standards and procedures

All surface and underground check or control surveys for the production of the mine plan should be carried out in accordance with this code of practice.

A district inspector may, in a particular case, approve in writing the carrying out by a person of a check or control survey of a mine by means other than those specified in the Mines Safety and Inspection Regulations 1995, r. 3.49(1), if the district inspector considers that the means will be sufficiently accurate.

The standard of accuracy referred to and required in this code of practice in general, is 1 in 5000 or better. Control surveys should be to 1:5000 or to within 0.5 m absolute error to mine datum. In the case of inaccessible workings or where reflectorless electronic distance-measuring (EDM) or laser-ranging equipment is employed for cavity measurement, a lower order of accuracy may be acceptable.

It is the responsibility of the authorised mine surveyor to become conversant with the survey methods, which will achieve the standards of accuracy set out above.

The choice of technique is a professional decision of the authorised mine surveyor, based on sound practice, and will be acceptable provided the methods employed comply with all existing legislation and the safe working practices of the mine.

2.2 Origin of coordinates

The authorised mine surveyor should ensure that if a local grid system is in use at a mine, the relationship between that grid and MGA94 is established in terms of distance, coordinates and with respect to orientation, and that these details are recorded in the survey book.

All surveys and plans should originate from the mine baseline. All control surveys must be connected to the mine baseline.

At each end of the mine baseline there should also be established a reference mark of durable nature connected by bearing and distance to the baseline.

2.3 Surface baseline

The surface mine baseline should not be less than 250 m in length and each end should be substantially marked.

Mine baseline stations for both opencut and underground mines should be permanent marks, preferably tagged with the station name and set in concrete. A witness plate should be placed adjacent to this mark.

Where permanent marks are placed for a surface baseline, these permanent marks should be shown on the mine plans. The authorised mine surveyor should ensure a hard copy and an electronic copy of all reference material are stored in the survey book.

2.4 Underground baseline

Each underground mine should establish a baseline in the underground workings of each level off a shaft or at least every 750 m of traverse in a decline access. The underground baseline should be in a suitable position and be as long as practicable, but at least 100 m in length. The marks should be stable and durable, and the location should be chosen to minimise movement or damage caused by blasting, ground movement or mobile equipment. The station number or identifier of the stations used must be painted on the adjacent wall. A durable tag indicating the station number or identifier should be attached to the station. Permanent baseline details should be recorded on the mine plan.

2.5 Traverses

The position of mine workings should be established with an accuracy of 1:5000 or to within 0.5 m absolute error to mine datum. In the case of inaccessible workings or where reflectorless EDM or laser-ranging equipment is employed for cavity measurement, a lower order of accuracy may be acceptable.

Instrumentation: The instrumentation used for control surveys and traversing should adhere to the following precision specifications:

- angular measurements (horizontal and vertical) — maximum standard error of $\pm 5''$
- distance measurements — maximum standard error of $\pm (3 \text{ mm} + 5 \text{ ppm})$
- GPS positioning — maximum standard error of horizontal positioning of $\pm (10 \text{ mm} + 10 \text{ ppm})$
- levelling — maximum standard error of levelling per kilometre of double run of $\pm 4 \text{ mm}$.

Accuracy: Each underground control survey and check survey should, where possible, be closed to the highest standard of accuracy that can be practically achieved. If loop closure is not practicable, the survey technique recommended is to undertake a two-way check traverse, closing within the accuracies mentioned in Subsection 2.1 of this code of practice.

Marking: Each underground control station should be adequately referenced and substantially marked. The station number should be painted adjacent to the survey station and again on the adjacent wall. A durable tag indicating the station number should also be attached as an adjunct to painting the number. As far as practicable, the marks should be placed in a position least likely to be disturbed by the effects of ground movement or mobile equipment. The stations should be shown on the mine plans.

All mine survey control stations should be part of a network of traverses with redundant observations allowing for rigorous adjustment of their positions and assessment of their positional accuracy.

2.6 Correlation of surface and underground surveys

Correlation between surface and underground surveys should be to the highest accuracy that it is practicable to obtain.

The correlation of surface and underground surveys may be by:

- traversing through an adit or a decline or incline ramp
- plumbing or plummeting one or more vertical shafts
- using a gyrotheodolite to establish azimuth
- a combination of these methods.

Where methods other than direct traverse through an adit or decline or incline ramp are employed for azimuth or coordinate transfer, the authorised mine surveyor should certify that the survey is accurate and meets the requirements of the Mines Safety and Inspection Regulations 1995.

Where vertical measurement is necessary for the transference of values from the surface baseline to a nominated underground baseline, care should be taken to minimise any error.

2.7 Accuracy of levelling

Datum

Where an established mine uses a local height datum (LHD):

- the relationship between the LHD and AHD should be detailed in the survey book
- the relationship with AHD should also be shown on the mine plans as required under the Mines Safety and Inspection Regulations 1995, r. 3.50(2).

Order of accuracy of survey control marks

Relative levels of forward stations should be checked with redundant measurements. In the case of conventional traversing, this could be either a re-survey or a level traverse. Failure to check the one-off measurements of instrument and target heights, either at the time of the initial survey or at some later stage, is unacceptable.

Order of accuracy of position of workings

All level traverses should be closed. The vertical closure rates of traverses should be better than $12K \text{ mm}$, where K is the traverse length in kilometres (i.e. a closure rate of 12 mm/km). More precise levelling may be required under some circumstances where precision is critical (e.g. in certain construction or installation work).

2.8 Survey records and supply of survey information

Systematic care should be taken for the safe and fireproof preservation of mine plans, notebooks, computer data files, traverse records and associated calculations, correlation records and associated calculations coordinate books or sheets, and other records from which the workings have been plotted.

Survey records for each of the following purposes should be kept at the survey office for the mine:

- surface surveys
- surface levelling
- underground control surveys, which should also be recorded in the survey book
- underground check surveys, which should also be recorded in the survey book
- surface check surveys
- underground levelling
- calculations
- any other relevant information.



Such survey records should be maintained either manually on a stable material or by electronic means that must be available at all times to all authorised personnel.

Where survey records are maintained in manual form, the following requirements are to be observed:

- All survey books should be maintained in good order and should have the following description attached:
 - titled with the mine name
 - sufficient information to indicate the location within the mine of the surveys contained in the survey book
 - consecutive index number.
- Where practicable, the following procedures should be adopted for entries into survey books:
 - all survey observations and measurements should be recorded at the time of survey
 - in the event of alteration of a mistake there should be no erasure. The erroneous entry should be struck through and the correction written above
 - the datum line of the survey and the azimuth adopted should be clearly indicated
 - lengths should be entered at the time they are measured and, where appropriate, corrections should be noted and the lengths deduced therefrom should be clearly indicated
 - bearing and distance from reference marks must be clearly shown
 - control stations and bench marks placed by the authorised mine surveyor should be so noted and their positions and descriptions should be shown by a sketch in the appropriate book
 - lines remeasured should be so specified and original distances and bearings shown
 - the authorised mine surveyor should sign the field book to indicate that the work shown therein was performed by him or under his supervision and indicate the date on which the work was performed.

Complete duplicate copies of survey records must be kept and stored separately from the originals, on paper, microfilm, magnetic tape, disk or other permanent medium.

The registered manager or the authorised mine surveyor of any mine, upon the request of the district inspector of mines, should make available on a stable material all or any survey records or certified copies thereof.

The mine plan must be revised as necessary, or every three months to show any significant changes in respect

of the workings that have been carried out in the intervening period.

Plans for lodgement with the Department of Industry and Resources (DoIR) must be compiled according to the Mines Safety and Inspection Regulations 1995, r. 3.52, and lodged within the correct timeframe as stated under this regulation.

When suspension or abandonment of mining operations is imminent, the employer, or if a receiver has been appointed in respect of a principal employer, that receiver, or the registered manager, must cause to be prepared, by the authorised mine surveyor, an update of the mine plan to accurately reflect the surveyed mine workings at the time of suspension or abandonment.

Upon discontinuance of mining operations, a copy of the mine plan should be submitted as soon as practicable to DoIR for retention, as described by the Mines Safety and Inspection Regulations 1995, rr. 3.14 and 3.52.

Upon abandonment of a mine, all survey records relevant to the preparation of the mine plan should be preserved on paper or microfilm and on magnetic tape or disc or other permanent electronic medium.

2.9 Requirements when workings are to become inaccessible

Before any part of the workings of a mine become inaccessible, where practicable and safe to do so, the position of all points of the workings should be established. Sufficient levels should be taken to clearly indicate the height of the floor of the workings on any mining level, bench or berm on the mine plan.

2.10 Maintenance and adjustment of survey equipment

Survey equipment used for baseline or other precise surveys should be maintained regularly and kept in good adjustment.

EDM equipment used for precise surveys should be verified against the surface baseline at least once each year and immediately after service or repair.

GPS equipment should be verified against an approved control network upon acquisition and after any change in software, firmware or hardware.



3 Mine plan

3.1 Authorisation of plan

The mine plan is required to be produced, maintained and kept under the Act, s. 87, and the Mines Safety and Inspection Regulations 1995, r. 3.51. The plan is to be signed by the authorised mine surveyor.

This code of practice also requires the lodgement of mine plans with DoIR at nominated intervals for:

- all underground mines
- all opencut mines.

3.2 Preparation of plan

The following should be observed in preparation of the mine plan:

- the plan must include any previous workings at the mine if any part of the mine has been worked in the past or if the mine was an abandoned mine
- the plan must be drawn to a scale that allows for legibility, including legibility when copied
- the plan must be revised when necessary to show any significant changes in respect of the workings that have been carried out at the mine
- the plan must be produced, on request, to a district inspector or to any other person authorised in writing by the district inspector to inspect it.

3.3 Composition of plan

The mine plan may be produced by either of the following:

Digital methods: prepared from the digital form of the plan held on a computer. It should be produced in hardcopy form for lodgement with DoIR. A digital document in a software format compatible with DoIR's software may also be lodged.

Manual methods: manually drafted and reproduced in hardcopy form for presentation.

In the case of an underground mine, the hardcopy of the digital mine plan or hand-drafted plan should consist of sheets for each mine level.

In the case of an opencut mine, the hardcopy of the digital mine plan or hand-drafted plan should consist of sheets for each deposit being worked.

In the case where a mine is worked from ramps and not from regular levels or sublevels, the mine plan should consist of whatever number of plan sheets is required to adequately show the extents of mine workings.

A reference in this code of practice to the mine plan includes a reference to plan, cross section and longitudinal section sheets of the workings of the mine, and correct copies or tracings of any original plan and sections.

3.4 Preparation by digital methods

When preparing the mine plan, the following information should be captured:

- mine lease boundary
- mine development
- survey stations and their identification
- mine shafts, adits and declines
- grid lines and values
- all workings in the deposit, including workings of adjacent mines within 50 m of the lease boundary
- for underground mines, an outline (boundary) of all old workings on the horizon being shown on that plan
- for underground mines, a detailed outline of current or associated workings in any direction of any development shown on a level plan sheet or section sheet on the horizon being shown on that plan
- underground service holes clearly annotated as to their use
- boreholes on the horizon being shown on that plan.

A copy of the revised mine plan should be prepared from the digitally held data and presented in the legible form described in Section 4 of this code of practice.

The plan and section sheets (as the case may be) on which workings occurred will be produced on durable



hardcopy medium. The previous copies may be archived or destroyed on preparation of the updated copy.

3.5 Manually drafted plans

Where the mine plan has been produced by non-digital means:

- the plan should be drawn on durable, stable polyester matt drafting material and should be in the form set out in Section 4 of this code of practice
- all drafting and printing are to be in ink.

Care should be taken to ensure that the inks used will bond satisfactorily with the material.

The overall sheet size of the plan should be, where appropriate, an International Standards Organisation (ISO) standard sheet size.

When compiling a mine plan by non-digital means, the following should be adhered to:

- the survey grid used should be clearly identified
- plotting of all surveys on a plan should be done so that all points in the survey are correctly plotted within 1 mm plan scale of their calculated coordinate position.

If the mine plan is produced photographically:

- the reproduction must be an accurate same-scale copy of the mine plan with no error or distortions
- the reproduction should be on durable, stable polyester matt drafting material.

3.6 Additional information

The authorised mine surveyor may include any additional information on the mine plan providing it is shown in a manner consistent with this code of practice.

The authorised mine surveyor should ensure that any information that may represent a danger to the mine, adjacent mines or adjacent strata if worked is recorded accurately on the plan.

3.7 Endorsement of plan

Endorsement of the mine plan should contain the following endorsement as required by the Mines Safety and Inspection Regulations 1995, r. 3.51(2):

“This is to certify that this survey has been done by myself (or by persons under my own supervision),

subject to adequate inspection and field check, and is the actual result of the observations and measurements, and the survey and plan have been done in accordance with the requirements of the *Mines Safety and Inspection Act 1994* and the regulations made under that Act.

DATED the..... day of 20.....

Authorised Mine Surveyor Grade
Certificate No. “

Where any information shown on the mine plan is in doubt or there is any other information that the authorised mine surveyor considers requires endorsement, the mine plan should be suitably endorsed. An example of a schedule of endorsements is shown below:

Schedule of endorsements			
Ref	Date	Description/References	Signed

The authorised mine surveyor, by signing and dating the certification, declares that:

- the mine plan has been prepared in accordance with the Act
- the surveys shown on the mine plan have been completed to an accuracy as prescribed in the Mines Safety and Inspection Regulations 1995.

3.8 Action upon discontinuance or abandonment

Authorisation

Regulation 3.52(d) of the Mines Safety and Inspection Regulations 1995 requires that the mine plan be amended and lodged when operations at a mine are discontinued or abandoned.

Action upon discontinuance or abandonment of a mine

Where any mine, of which a mine plan is required, is discontinued or abandoned, a survey of the final



position of the workings will be undertaken and the mine plan amended. Upon the discontinuance or abandonment of a mine, the mine plan should be certified, dated and signed by the authorised mine surveyor to the date of discontinuance or abandonment.

Upon the discontinuance or abandonment of a mine, the mine plan should be produced on durable polyester matt film as soon as practicable after such discontinuance or abandonment, and forwarded to DoIR.

A digital record, in a form suitable for archiving and future reference, and a plan on durable polyester matt film should be produced for retention at the mine office.

3.9 Cessation of duties of the appointed mine surveyor

Upon permanent cessation of duties of the appointed mine surveyor, the mine plan should be amended, dated and signed by the appointed mine surveyor. The appointed mine surveyor should show the date of the workings at the time of cessation on these plans.

The outgoing mine-appointed mine surveyor should, where possible (with the consent of the mine owner), take a copy of the sheets for his or her own record.

The incoming appointed mine surveyor should, make a copy of the sheets for a record of commencement of work.

3.10 Other plans required

Combined plans

The authorised mine surveyor may combine one or more of the following plans into the sheets of the mine plan, provided legibility of the combined plans is retained.

Ventilation plan (underground mines)

The authorised mine surveyor must ensure that all major ventilating fans, air doors, brattices or other ventilating devices or controls in use at the mine are recorded on the plans and sections of the mine.

Surface plan

In the case of an opencut mine, the surface plan should show all detail as set out in Section 4 of this code of

practice, and all streets, roads, reservoirs, swamps, water bodies and any other permanent features that, if disturbed by mining operations, could cause damage to or danger in the mine.

Accident plan

Regulation 3.54 of the Mines Safety and Inspection Regulations 1995 outlines the requirements for survey when a serious accident or dangerous incident occurs. The accident location must not be disturbed.

In the case of any accident causing a fatality, a survey of the accident location is required, and an accident plan must be produced.

In the case of a serious but non-fatal accident, an inspector may require a survey to be carried out or an accident plan to be prepared.

Where possible, photographs of the accident location should accompany the accident plan.

Where conditions or continuing danger prevent a location survey being made, the position of the accident should be indicated on a copy of a mine plan sheet, and annotated by the authorised mine surveyor.

The information required on an accident plan is set out in detail in Section 4 of this code of practice. The detail shown must include:

- an outline of the mine workings
- the location within the mine
- the location of all fixed and mobile plant
- the location of personal apparatus, equipment or clothing
- sufficient annotation and labelling to clearly describe the condition and name of each object at the accident location.

Emergency plan

An emergency plan should be produced using the mine plan as its basis.

The emergency plan should be revised at least every three months, following the most recent revision of the mine plan, and contain relevant and up-to-date information on the following:

- mine egress
- firefighting system and appliances
- mine rescue and safety.

The emergency plan should be at a scale of not less than 1:2000, and consist of a number of plan sheets adequately describing the major mine workings.



This plan should show:

- shafts, ramps and the main level development
- the means of egress from each part of the mine to the surface and underground telephone stations
- the positions of pipe mains, hydrants, isolation valves, fire substations and fire depots
- the positions of stoppings, trapdoors, regulators, seals, prepared seal sites, overcasts, air crossings, ventilation doors, belt conveyors, main electric supply cables, fixed electrical apparatus, telephones and the direction of ventilation in the main development headings
- the location of refuge chambers, first aid stations, underground telephone locations, and any air quality or gas monitoring points, together with the route of such monitoring
- bad or inaccessible ground, accumulations of water, filled voids, and any information identified as necessary for dealing with an emergency at the mine.

A copy of the emergency plan must be maintained on view at the mine, with an up-to-date copy kept in an accessible place in case of emergency.

3.11 Plan lodgement requirements

Underground mines

The mine plan should be lodged with DoIR within one year of the commencement of mining operations and, thereafter, every five years.

Where a mine is to be discontinued or abandoned, a final mine plan in hardcopy is to be lodged with DoIR as soon as practicable after the date of discontinuance or abandonment.

Opencut mines

The mine plan should be lodged with DoIR within one year of the commencement of mining operations and, thereafter, every five years or unless otherwise directed by the district inspector.

Where a mine is to be discontinued or abandoned, a final hardcopy mine plan is to be lodged with DoIR as soon as practicable after the date of discontinuance or abandonment.



4 Mine plan format and information

4.1 Sheet format

Plan sheet

Each mine working sheet should show the following detail as required by the Mines Safety and Inspection Regulations 1995, r. 3.51:

In the sheet heading

- the name of the mine (e.g. Red Rocks gold mine)
- the number of the level or mine horizon according to the adopted mine nomenclature.

In the sheet surround

- the reduction ratio and a graphical (bar) scale, together with a statement that all measurements are in metres, or grid line values labelled appropriately
- a north point indicating true north in relation to the local grid and MGA94
- a schedule of symbols used on the particular sheet as detailed in the survey book
- a sheet index showing all the sheets necessary to cover the mine holding and the number of each sheet with the particular sheet shown by a heavy outline
- a schedule of survey dates and certifications
- the origin of levels, and the grid bearing and major survey stations of the surface baseline
- a table of survey marks and benchmarks containing their identification, coordinates and height (or shown on plan area).

In the plan area

All detail should be plotted at a scale that will allow copying and legibility, and the following detail will be shown:

- a grid showing coordinates
- the position of survey stations or benchmarks and their identification
- labelled lines showing the position of the cross sections shown on the cross section sheets
- mining lease boundaries
- all abandoned or historical workings within 50 m of the current lease boundaries and on the horizon being shown on that plan.

Section sheets

Separate cross section sheets should be provided in order to adequately represent the form and extents of mine workings.

Each cross section should be compiled from information gained from the actual workings and not from borehole information.

Each cross section sheet should show the following detail as required by the Mines Safety and Inspection Regulations 1995, r. 3.51:

In the sheet heading

- the name of the mine
- the grid coordinate or reference line to which the section refers.

In the sheet surround

- the reduction ratio and a graphical (bar) scale, together with a statement that all measurements are in metres, or grid line values labelled appropriately.

4.2 Mine plan information

Detail required

The type of detail to be shown on the mine plan is described below. It is expected that the plans will be as comprehensive as practicable in terms of detail shown.

The types of information listed to be shown on the mine plan are the minimum requirements only, and it is at the discretion of the authorised mine surveyor whether any additional information is shown.

Mine plans — underground mines

Surface plan

A surface plan of the mining lease should show the true position of the following features:



- mining lease boundaries
- all buildings, both fixed and portable, including offices, workshops, warehouses, power stations, crushing and grinding plant, metallurgical plant, and storage and loading facilities
- access roads and car parks
- the position of haulage (brace level) and ventilation shafts, and ventilation fans
- conveyors and stockpile areas, including reclaim tunnels
- transformer yards
- overhead and underground power transmission lines
- explosives and detonator magazines
- ANFO plants and storage
- rail sidings
- bulk chemical storage bins and process vessels
- fuel storage tanks and fuelling areas
- the extents of open shafts, stopes or open pits at the surface
- the extents of caved ground due to underground mining
- decline portals and access roads
- site fencing and gates
- tailings dams
- waste dumps
- drainage and water retention structures, dams and water tanks
- surface and underground pipelines
- drainage and service boreholes
- boreholes that may affect the safety of the mine
- natural features, including water courses and lakes
- any disused buildings, plant or shafts from older or defunct mine workings within the mining lease or claim area
- surface spot levels or contours
- survey reference marks and baseline.

Underground level plans

The level plans should show development at each primary haulage or drilling level, and the correct positions of the following features:

- man, haulage and ventilation shafts
- all development drives and crosscuts, and working faces
- stope outlines at the level
- winzes, raises, ore passes, fill passes, ladderways and chutes
- refuge chambers

- electrical substations
- rail track
- crib rooms and offices
- workshops, including overhead cranes and monorails
- explosives and detonator magazines
- skip loading pockets
- ore bins
- conveyor drives and crushing stations
- pumping stations and sumps
- boreholes that may affect the safety of the mine
- the outline of development or stoping within 5 m of a mine level
- ramps and access declines.

A composite plan showing ramps or access declines and inclines between levels should be provided where these are not partially shown on the level plans.

Mine plans — opencut mines

Surface plan

A surface plan of the mining lease should show the true position of the following features:

- mining lease boundaries
- all buildings, both fixed and portable, including offices, workshops, warehouses, power stations, crushing and grinding plant, metallurgical plant, and storage and loading facilities
- access roads and car parks
- the position of haulage (brace level) and ventilation shafts, and ventilation fans
- conveyors and stockpile areas, including reclaim tunnels
- transformer yards
- overhead and underground power transmission lines
- explosives and detonator magazines
- ANFO plants and storage
- rail sidings
- bulk chemical storage bins and process vessels
- fuel storage tanks and fuelling areas
- the extents of open shafts, stopes or open pits at the surface
- the extents of caved ground due to underground mining
- decline portals and access roads
- site fencing and gates
- tailings dams
- waste dumps



- drainage and water retention structures, dams and water tanks
- surface and underground pipelines
- drainage and service boreholes
- boreholes that may affect the safety of the mine
- natural features, including water courses and lakes
- any disused buildings, plant or shafts from older or defunct mine working within the mining lease or claim area
- surface spot levels or contours
- survey reference marks and baseline.

Opencut plans

The openpits may be shown on the surface plan. However, where site facilities, such as crushing, milling and administration, are at a distance from the openpits, then a series of plans should be provided to show the relevant detail. This detail includes the positions of the following:

- tops and toes of all batters
- berms and benches
- haulage and access ramps between berms
- in-pit crushing plant and storage bins
- spot height levels of berms or benches
- pumps and sumps
- overhead powerlines
- adjacent underground workings (current and abandoned) in relation to the openpit.

Accident plans

Section 3.10 of this code of practice sets out the requirements for producing an accident plan. The plan should be surveyed and drafted according to the following clauses.

The accident plan means one or more plan sheets, section sheets or other plan provided to correctly describe the accident location.

A locality plan or sketch must be included showing the area described by the accident plan in relation to the whole of the mine workings.

The scale of the plan should be chosen to adequately show the detail. This would typically be a scale of no more than 1:50. A sheet of the mine plan may be used as a base provided the scale is adequate for the purpose of showing the detail. The current position of working faces must be shown.

The following information will be shown in the sheet surround of every sheet used:

- the mine name, level name, and such information as to accurately describe the area of the mine where the accident occurred
- the reduction ratio and a graphical (bar) scale, together with a statement that all measurements are in metres
- a north point indicating mine grid north
- a schedule of symbols used on the particular sheet or each symbol annotated as detailed in the survey book
- the label "Accident plan" should be written prominently in the sheet surround to clearly differentiate the plan from any sheet of the mine plan.

The accident plan title block should include the following information:

- scene of (fatal) accident to (name)
- (location) (shift) (date)
- (company name)
- drawing number
- scale
- authorised mine surveyor's certification and annotation as to accuracy and completeness
- field or level book numbers used in accident plan survey.

The plan must show all detail that existed just prior to the accident, together with any detail that has been positioned as a result of the accident. All detail must be accurately labelled.

One section or sectional elevation is to be drawn to the same scale as the plan view, and the section's position must be shown on that plan. The same level of detail is to be shown on the section as required for the accident plan.

The detail shown must include the following:

- the real or assumed position of the injured person or persons — it would be expected that the injured or fatally injured person will have been removed from the scene
- the positions of other personnel at the time of the accident
- the position of articles of protective clothing such as helmets and gloves
- equipment used in rescue operations
- general environment and position of mining equipment and plant
- positions from which photographs were taken
- other relevant information as directed by an inspector.

The plans concerning fatal accidents should not be viewed or made available to any person other than:



- an inspector of mines
- an authorised member of DoIR's investigations unit
- the mine general manager
- the Coroner
- a board of inquiry into the accident.

The accident plan should be stored in a secure place under the direct control of the authorised mine surveyor.

Emergency plans

An emergency plan should be produced in a format according to the clauses listed in Section 3.10 of this code of practice.

An emergency plan should be produced using the updated mine plan as its basis.

The label "Emergency plan" should be written prominently in the sheet surround of every sheet.

A copy of the emergency plan must be maintained on view in a prominent place at the mine, with an up-to-date copy kept in an accessible place in case of emergency.

The emergency plan should be at a scale that allows legible reproduction and consist of a number of plan sheets adequately describing the major mine workings.

The information contained on the emergency plan should be as follows:

Mine egress information

- shafts, ramps and the outline of the main level development
- the means of egress from each part of the mine to the surface, including ladderways, plats and emergency hoists
- underground telephone stations

- non-accessible areas of the mine
- fresh air stations.

Firefighting system and appliances information

- alarm and smoke warning systems
- fire pipe mains
- water mains and valves (general)
- hydrants
- isolation valves
- fire substations
- fire depots
- stoppings, trapdoors, regulators, seals, prepared seal sites, air crossings and ventilation doors
- belt conveyors
- main electric supply cables and fixed electrical apparatus
- telephones
- direction of ventilation in the main development headings.

Mine rescue and safety information

- refuge chambers
- first aid stations
- telephone locations
- air quality or gas monitoring points together with the route of such monitoring
- bad or inaccessible ground
- accumulations of water
- filled voids
- any other information identified as necessary for the dealing with an emergency at the mine.



Appendix 1

Legislative framework

Mines Safety and Inspection Act 1994

- General duties
- Management of mines
- Enforcement of the Act and regulations
- Resolution of issues
- Safety and health representatives
- Safety and health committees

supported by

Mines Safety and Inspection Regulations 1995

The Mines Safety and Inspection Regulations 1995 set minimum requirements for specific hazards and work practices, including reference to national standards, developed by the National Occupational Safety and Health Commission, and Australian standards developed by Standards Australia.

and

Guidance material

- Codes of practice approved for Western Australian mines in accordance with the Act, s. 93
- Guidelines approved by the Mines Occupational Safety and Health Advisory Board
- National codes of practice and national standards developed by the National Occupational Health and Safety Commission
- Australian Standards developed by Standards Australia

Part 7, Division 3 of the *Mines Safety and Inspection Act 1994* (the Act) and Part 3, Division 6 of the Mines Safety and Inspection Regulations 1995 set out the aims to be achieved in order to prevent hazards to persons arising as a result of less-than-adequate survey practice in mines. These provisions apply to all mines under the Act. (In addition, these aims and compliance with these provisions potentially afford protection to the external environment from some possible adverse consequences of mining.)

For convenience, the relevant provisions under the Act and regulations are reproduced in this code of practice, which also provides methods of meeting those requirements.

The code of practice provides practical guidance on the more important areas of mine survey relating to safety issues and sets approved standards. However, it cannot specify every possible detail or circumstance. Those who have duties under the Act or regulations should



remain alert to developments and hazards that may not be fully dealt with by the code of practice or other guidance material, and should use their expertise to assess what further measures may be necessary or desirable in the light of good working practice and local circumstances.

Although failure to observe any provision of the code of practice is not, in itself, an offence, that failure may be taken by a court in criminal proceedings as proof that a person has contravened a regulation or section of the Act to which that provision relates. In such a case, however, it will be open to that person to satisfy the court that the regulation or section has been complied with in some other way.

Further information on the legislative framework can be found in the Chamber of Minerals and Energy's publication "General duty of care in Western Australian mines".

The legal status of codes of practice

The provision for approval of codes of practice is made in the Act, s. 93(1):

- 93.** (1) The Minister may approve a code of practice which has been considered by the Mines Occupational Safety and Health Advisory Board, for the purpose of providing practical guidance to employers, self-employed persons and employees and other persons on whom a duty of care is imposed under this Act.

Section 93 sets out the processes associated with the approval and revision of codes of practice, and the status of approved codes of practice in relation to legal proceedings. The following points are included:

- a person is not liable to any civil or criminal proceedings simply because of non-compliance with a code of practice
- where it is alleged that a person has contravened a provision of the Act or regulations, the information in a code of practice may be used as evidence to show there is a practicable means of reducing the risk of work-related injury or disease.

However, demonstration that the person has complied with the Act or regulations by some other means would be a satisfactory defence.

Codes of practice may not provide exact solutions to occupational safety and health problems in all workplaces in the industry, but following the practical guidance in this code of practice should help to reduce the risk of serious injury or death.

Specific legislative and regulatory material governing mines survey practice

Mines Safety and Inspection Act 1994

Part 7 — Specific duties relating to occupational safety and health

Division 3 — Plans and records

Plans to be furnished

- 87.** (1) The manager of a mine must procure and keep in the office of the mine accurate plans of the mine that —
- (a) in accordance with the regulations, are kept up to date; and
 - (b) are prepared on a scale that accords with good engineering practice; and
 - (c) contain the particulars required by the regulations.
- (2) The manager of a mine must provide to the State mining engineer free of charge copies of the plans referred to in subsection (1) in accordance with the regulations.
- (3) If the State mining engineer has reason to believe that a plan provided under this section is inaccurate or incomplete, the State mining engineer may direct the principal employer to have a check survey conducted at the principal employer's own cost and the principal employer must comply with such a direction without delay.
- (4) The plans referred to in subsection (1) must be produced by the manager at the mine to an inspector, an assistant inspector, or any other person authorised for the purpose in writing by the State mining engineer, and the manager must, if requested by that inspector, assistant inspector, or other person, mark on such plans the progress of the operations of the mine up to the time the plans are produced to the inspector, assistant inspector, or other person, and must allow that person to examine and take a copy of those plans.
- (5) A person who contravenes subsection (1), (2), (3), or (4) commits an offence.
- (6) A manager who knowingly causes or permits to be omitted from any plan prepared for the purposes of this section any part of the workings of a mine commits an offence.

- (7) This section does not apply to mines at which the mining operations consist only of exploration operations.

Plans for abandonment or suspension

88. (1) Where mining operations are about to be abandoned or suspended, the principal employer, or if a receiver has been appointed in respect of a principal employer, that receiver, or the manager must cause to be prepared to the satisfaction of the district inspector for the region in which the mine is situated an accurate plan or plans of the mining operations to the time of abandonment or discontinuance and must furnish that plan or those plans to the State mining engineer in accordance with the regulations before the mining operations are abandoned or suspended.

- (2) A principal employer, receiver, or manager who contravenes subsection (1) commits an offence.

Mines Safety and Inspection Regulations 1995

Part 3 — Management of mines

Division 6 — Surveys and plans

Instruments and accuracy

- 3.49. (1) A person who carries out a survey at a mine must ensure that —
- (a) the survey is carried out using instruments and equipment of precision equal to best current industry standards and technology; and
 - (b) the survey is carried out to a standard that accords with good engineering practice and is to an accuracy of not less than 1:5000.

Penalty: See regulation 17.1.

- (2) Subregulation (1) does not apply to a person who carries out a survey of a mine in accordance with an approval given by the district inspector under subregulation (3).
- (3) The district inspector may, in a particular case, approve in writing the carrying out by a person of a survey of a mine by means other than those specified in sub regulation (1) if the district inspector considers that the means will be sufficiently accurate.

Datum station and co-ordinates

- 3.50. (1) A person who carries out a survey of a mine must establish, in the general vicinity of the mine, a

datum station which is to serve as the origin for the survey and the co-ordinate system used.

Penalty: See regulation 17.1.

- (2) The position of the datum station referred to in subregulation (1) must be established in terms of the Map Grid of Australia 1994 co-ordinate system and the Australian Height Datum (AHD).
- (3) A person who carries out a survey of a mine must ensure that if a local grid system is used for mine surveying and management the relationship between that grid system and the Map Grid of Australia 1994 in terms of distance and with respect to true bearing is established.

Penalty: See regulation 17.1.

Particulars required in mine plans

- 3.51. (1) For the purposes of section 87(1)(c) of the Act, the following particulars must be contained in plans referred to in that section —
- (a) a plan of the lease or tenement in which the mine is situated showing —
 - (i) the datum station established as the origin of the survey;
 - (ii) the relationship to the Map Grid of Australia 1994; and
 - (iii) the relationship to the local grid system;
 - (b) in relation to quarry operations, a plan showing the true size and shape of all excavations and sufficient cross-sections showing advances made in the quarry operations and the areas reclaimed or again filled in;
 - (c) a general plan of any underground levels to a scale that accords with good engineering practice that shows, so far as is practicable, the true size and shape of all development openings, but a composite plan may be accepted if each level on that plan can be clearly seen;
 - (d) if any underground drill holes at the mine contain potentially hazardous services including electrical power cables, compressed air lines or diesel fuel lines, details of the location of those holes;
 - (e) so far as is practicable, longitudinal sections or projections to a scale that accords with good engineering practice that shows all underground mining operations;



- (f) so far as is practicable, sufficient cross-sections or projections to a scale that accords with good engineering practice that clearly shows the ore bodies and the parts of ore bodies mined out;
 - (g) the date when the plan was made; and
 - (h) certification by the person who made the plan that the plan is correct.
- (2) In relation to a plan of underground mine operations the certification referred to in subregulation (1)(h) must be in the following form —

"This is to certify that this survey has been done by myself (or by persons under my own supervision), subject to adequate inspection and field check, and is the actual result of the observations and measurements, and the survey and plan have been done in accordance with the requirements of the *Mines Safety and Inspection Act 1994* and the regulations made under that Act.

DATED the day of 20.....

Authorised Mine Surveyor Grade
Certificate No.

When plans must be provided to State mining engineer

- 3.52.** For the purposes of section 87(2) of the Act, the plans referred to in subsection (1) of that section must be provided to the State mining engineer —
- (a) within one year after the commencement of mining operations at the mine;
 - (b) in the case of any mine where there are underground operations, at intervals not exceeding 5 years following the initial provision of plans;
 - (c) before any planned period of suspension of mining operations at the mine; and
 - (d) as soon as practicable after the mine is closed.

Form of plans

- 3.53.** For the purposes of section 87(2) of the Act, the plans referred to in subsection (1) of that section must be provided to the State mining engineer —
- (a) in the case of the initial set of plans, in hard copy form;
 - (b) in the case of plans provided before any suspension of mining operations at the mine or when the mine is closed, in hard copy form accompanied, so far as is practicable, by a copy in electronic form; and
 - (c) in the case of any plans provided at times other than those referred to in paragraph (a) or (b) —
 - (i) if the State mining engineer approves, in micro film or in electronic form;
 - (ii) if the State mining engineer does not approve of the plans being given in micro film or electronic form, in hard copy form.

Plan of scene of fatal accident

- 3.54.** (1) This regulation applies if the Coroner or deputy Coroner or an inspector requires a survey to be carried out or a location plan to be prepared of the scene of any fatal accident at a mine (whether underground or elsewhere at the mine).
- (2) If this regulation applies, the manager of the mine must ensure that a person is not engaged to carry out the survey or to prepare the location plan unless the person is the holder of an authorised mine surveyor's certificate.

Penalty: See regulation 17.1.

Note: The only authorised versions of the Act and regulations are those available from the State Law Publisher (www.slp.wa.gov.au), the official publisher of Western Australian legislation and statutory information.

Appendix 2

Glossary

Abandoned: A mine is deemed to be abandoned where the working of the mine or deposit has ceased, and there is no ongoing care-and-maintenance program in place

Act: The *Mines Safety and Inspection Act 1994*

Adit: A horizontal or moderately graded development opening into a mine through which persons and materials are transported and services, including ventilation, are maintained, or any combination of these functions or services is maintained

AHD: Australian Height Datum 1971

ANFO: Ammonium nitrate — fuel oil explosive

Annotation: A note on the mine plan providing additional explanation of some feature or characteristic of the workings not otherwise evident from viewing the plan. For example, the words “No access”, on a level plan would indicate a non-trafficable or inaccessible section of the mine. Similarly, the notation “Old workings nearby — no survey” would alert the plan viewer to the possibility of workings of unknown extents and condition in the vicinity of the working mine

Appointed mine surveyor: An appointed mine surveyor is a person who is an authorised mine surveyor as defined under regulation 3.47(3) and is nominated by the manager of a mine under regulation 3.46 (3) of the Mines Safety and Inspection Regulations 1995

Authorised mine surveyor: The person referred to in regulation 3.47(3) of the Mines Safety and Inspection Regulations 1995. The duties of the authorised mine surveyor are to:

- ensure that surveys are carried out using instruments and equipment of precision equal to best current industry standards and technology
- ensure that surveys are carried out to a standard that accords with good engineering practice and to an accuracy of not less than 1:5000
- prepare or supervise the preparation, update and maintenance of the mine plan and associated survey records to this recommended standard

Bad ground: Any ground made inaccessible or non-trafficable because of instability. The term includes any area of a mine where there is heavily faulted, stressed or caved ground, or where there has been pillar fracturing or failure

Batter of a face or profile of opencut: The angle that the face or side of an opencut mine makes with the horizontal

Bench: The horizontal step or floor along which ore, stone or overburden is worked or mined

Berm: A level surface or bench left or specially cut in the side of an opencut mine for the purposes of trapping falling material and for pit wall stability

Bin: A structure used to hold loose material

Borehole: Any hole, including auger holes, which may affect the safety of the mine, drilled for:

- exploration (either vertically, horizontally or inclined)
- gas or water drainage
- transport of materials, including (but not limited to) sand, inflammable materials or fuels, cement, slurry, sewage and water
- services such as power and water

Brace: A platform area around a shaft on the surface of a mine.

Certification: A written statement or a schedule signed by the authorised mine surveyor attesting that the surveying procedures and plan preparation for the period certified have been carried out pursuant to the standard required by the Act and Mines Safety and Inspection Regulations 1995

“This is to certify that this survey has been done by myself (or by persons under my own supervision), subject to adequate inspection and field check, and is the actual result of the observations and measurements, and the survey and plan have been done in accordance with the requirements of the Mines Safety and Inspection Act 1994 and the regulations made under that Act.

DATED the day of 20.....

Authorised Mine Surveyor Grade
Certificate No.”

Check survey: A survey traverse carried out to the same or higher order of accuracy to check or improve a previously run survey, or the closing of two open-ended control surveys through a new opening

Control surveys: Substantially marked surveys developed from a mine baseline to define the direction and position of the workings of a mine

Cross section sheet: A sheet prepared as part of the mine plan for opencut or underground operations that shows the cross sections referred to on the plan sheets of the mine plan



DoIR: The Department of Industry and Resources, Western Australia, its predecessors and successors

Decline: A development opening driven down from the surface to any level or between any two levels in a mine at gradients permitting the use of trackless equipment

Development: In relation to a mining operation, includes all work undertaken to open up a mine by driving access openings or pre-stripping an opencut body of ore

Development opening or development heading: In relation to an underground mine, means any drive, crosscut, tunnel, adit, incline, decline, ramp, winze, rise or shaft that is driven to provide access and services to underground operations, however excavated

Discontinued or suspended: Where an opencut or underground mine or a deposit has ceased being mined, but the mine is subject to a care-and-maintenance program, that opencut or underground mine or deposit is deemed to be discontinued

Endorsement: A significant notation by the authorised mine surveyor on a plan prepared in accordance with this code of practice. Any such notations may draw attention to any aspect of the compilation of the mine plan that is considered necessary or informative. For example, any major event at the mine that creates a significant hazard, such as an inrush of mud, a pillar failure or the failure of a stope fill bulkhead, would warrant endorsement

Face: The current or most recently surveyed position of advance of a mine development or excavation

First aid facilities: Includes first aid kits, special first aid equipment, safety showers and eyewashes

Geocentric Datum of Australia 1994 (GDA94) and Map Grid of Australia 1994 (MGA94) coordinate system: The datum for surveys in Western Australia is known as the Geocentric Datum of Australia 1994 (GDA94). GDA94 is based on the Geodetic Reference System 1980 (GRS80) ellipsoid. The eight points used to define the GDA94 are known as the Australian Fiducial Network (AFN) and were computed in terms of the International Terrestrial Reference Frame 1992 (ITRF92). Grid coordinates are obtained using a Transverse Mercator projection known as the Map Grid of Australia 1994 (MGA94) having the following specifications:

Designation of MGA94 zones

- The central meridians and the designation of the several zones are as follows:

Central meridian	Designation
Longitude east of Greenwich	of MGA94 zone
117°	50
123°	51
129°	52

- The central meridian scale factor is 0.9996
- The zone width is 6° longitude plus 0.5° overlaps on each side
- The coordinates of a point on the earth's surface, to be used in expressing the position or location of each point in the appropriate zone, consists of two distances expressed in metres and decimals of a metre; the first expressed of these distances, the East, or E, coordinate gives the position in an east direction, the second expressed, the North, or N, coordinate gives the position in a north direction
- The origin of coordinates of each zone is at the intersection of the central meridian of that zone with the equator, which origin is given the value of E 500 000m; N 10 000 000 m
- The units used will be the international metre
- Coordinates stated for any point in the system should be coordinate values determined in accordance with the principles of the projection of the MGA94, and should depend upon and conform to the coordinates of the State survey control marks

GPS: Global positioning system. This term covers all types of satellite positioning system in this code of practice. This includes both the US Department of Defence GPS NAVSTAR system and the Russian GLONASS system, and includes any other current or future satellite positioning system with the same purpose or functionality

Hazard: In relation to a person, means anything that could result in injury to the person or harm to the health of the person

Height datum: All levels should be related to Australian Height Datum (AHD). Where a mine survey is based on another datum, the method of reducing to AHD must be indicated on the mine plan and should be recorded in the survey book

Incline: A development opening driven up from any level to the surface or between any two levels in a mine at gradients permitting the use of trackless equipment

Inspector: An inspector of mines appointed under the Act, s. 17

Longitudinal: A sheet prepared as part of the mine plan for opencut or underground operations, which shows the longitudinal sections referred to on the plan

Magazine: A building, storehouse, structure or place in which any explosive or blasting agent is kept or stored, whether in or about a mine, and including detonator storage buildings and buildings containing capped fuses

Mine baseline: A permanently marked survey line established on the surface or part of the State survey control network. The mine baseline may be computed from conventional or GPS observations



Mine evacuation, emergency or rescue plan: Plan prepared showing required information for the surface of the mine or the underground workings, and any other information that could assist in the case of an emergency

Mine manager: The person appointed under the Act, s. 33, as the registered mine manager

Mine surface plan: Plan prepared in accordance with Section 3 of this code of practice showing surface features

Mine plans: The plans required to be kept under the Mines Safety and Inspection Regulations 1995, r. 3.51, to accurately show the position of the mine workings, and compiled in accordance with this recommended code of practice

Digital: A digital image file of the mine plan in accordance with Section 3 of this code of practice

Hardcopy: A copy of the mine plan plotted on the appropriate medium in accordance with Section 4 of this code of practice

Opencut, openpit or quarry: A surface mining operation in which mineral or rock is extracted from the earth by excavating into a natural surface gradient and including:

- harvesting evaporites
- strip mining
- extraction of sand, clay and gravel
- hydraulic mining
- solution mining through boreholes or existing openings within the earth, whether natural or resulting from previous mining

Ore pass: An underground opening through which broken material is transferred, by gravity, from a higher level to a lower level

Plan and sections: Includes correct copies of any original plan and section sheet forming part of the mine plan. Sections include both cross and longitudinal sections

Plat: A platform area around a shaft at an underground level

Quarry: See opencut, openpit or quarry

Raise or rise: A vertical or steeply inclined development opening driven upward from any level in an underground mine

Ramp: A development opening driven up or down from any level development or the surface, or between any two mining horizons in a mine at gradients permitting the use of trackless equipment

Refuge chamber: A refuge to provide a “safe haven” for those persons working in the immediate area in the event of the atmosphere becoming irrespirable

Shaft: A vertical or inclined development opening into or within a mine through which persons and materials are raised and lowered using winding engines, and through which services including ventilation may be provided; or a vertical or inclined development opening into or within a mine used for ventilation. It does not include a winze constructed from the surface nor an underground level that may be used temporarily for the raising and lowering of persons or materials unless, in the opinion of an inspector, the winze is used as a shaft

Stope: An excavation, other than development workings, made for the purpose of excavating ore

Supervision: When a survey is carried out in accordance with this code of practice, the authorised mine surveyor must exercise such immediate oversight and personal direction of the work as is necessary to ensure that the authorised mine surveyor has the knowledge to certify all aspects of the survey and that the survey has been carried out in accordance with sound professional practice and the Mines Safety and Inspection Regulations 1995

Survey book: A book that is retained in a safe location on the mine that contains cross-referenced information relating to survey records

Survey records: This is taken to mean field books, level books, coordinate books, computer data files, calculations and any other note books, sheets or plans used for recording relevant survey data, all survey observations, compilations and other relevant survey data whether recorded or stored in manual form or by electronic or other device

Underground: In relation to mining operations, means any operations beneath the natural surface of the earth that are covered overhead by natural rock or earth, or by any earth, rock, fill, timber or other material placed in the course of mining operations, and including tunnels, drifts, shafts and winzes used in mining operations and more than 2 m deep sunk from the surface

Underground baseline: A permanently marked survey line established in underground workings from which underground surveys are developed

Vertical or subvertical openings: Includes stopes, access rises, fill passes, ore and waste passes, ventilation rises and shafts, and escape ways

Winze: A vertical or steeply inclined development opening sunk downward from any level in an underground mine, or from the surface into a mine

Working face: The area of excavation that is being worked



Department of
Industry and Resources

Safety and Health Division

Mineral House
100 Plain Street
EAST PERTH WA 6004

Telephone: +61 8 9222 3092
Facsimile: +61 8 9325 2280
Email: shed@doir.wa.gov.au
Website: www.doir.wa.gov.au